

通用型微动开关 Z-20, Z-25 系列

动作特性定义

- OF 动作力
- RF 复位力
- OT 超行程
- TT 总行程
- PT 动作行程 (预行程)
- MD 距差
- OP 动作位置
- PO 绝对开离位置

规格

操作速度	0.01mm-1m/sec
操作频率	机械 240ops/min ; 电气 20 ops/min
绝缘电阻	>100MΩ@500V DC
接点电阻	<15mΩ (initial value)
额定电流/电压	Z-20G: 20A, 125/250/480VAC; 1.5HP/125VAC or 2HP/250VAC Z-25G: 25A, 125/250/480VAC; 1.5HP/125VAC or 2HP/250VAC
耐压值	同级端子间1000VAC 50/60Hz 1分钟 端子对地或对无载金属间2500VAC 50/60Hz 1分钟
寿命	机械 1×10 ⁷ 次 电气 5×10 ⁵ 次
环境温度	-25~+80°C (-13~176°F) 不结冰
湿度	< 95%RH
保护等级	IP00/IP63

安装尺寸 单位:mm

<p>Z-20G & Z-25G</p>	<p>Z-20GD & Z-25GD</p>
<p>动作特性</p> <ul style="list-style-type: none"> ● OF 3.89~6.11N ● RF (Min) 2.78N ● PT (Max) 1.3mm ● OT (Min) 0.25mm ● MD 0.05~0.2mm ● OP 16.27±0.4mm 	<p>动作特性</p> <ul style="list-style-type: none"> ● OF 3.89~6.11N ● RF (Min) 2.78N ● PT (Max) 1.3mm ● OT (Min) 3.0mm ● MD 0.05~0.2mm ● OP 26.2±0.5mm
<p>Z-20GW & Z-25GW</p>	<p>Z-20GW1 & Z-25GW1</p>
<p>动作特性</p> <ul style="list-style-type: none"> ● OF (Max) 0.7N ● RF (Min) 0.14N ● PT (Max) 15.9mm ● OT (Min) 1.98mm ● MD (Max) 2.77mm ● OP 19.1±0.8mm 	<p>动作特性</p> <ul style="list-style-type: none"> ● OF (Max) 1.6N ● RF (Min) 0.4N ● PT (Max) 6.5mm ● OT (Min) 1.2mm ● MD (Max) 1.2mm ● OP 19.1±0.8mm
<p>Z-20GW2 & Z-25GW2</p>	<p>Z-20GW22 & Z-25GW22</p>
<p>动作特性</p> <ul style="list-style-type: none"> ● OF (Max) 0.97N ● RF (Min) 0.14N ● PT (Max) 11.9mm ● OT (Min) 1.52mm ● MD (Max) 2.16mm ● OP 30.2±0.8mm 	<p>动作特性</p> <ul style="list-style-type: none"> ● OF (Max) 1.67N ● RF (Min) 0.42N ● PT (Max) 6.35mm ● OT (Min) 0.76mm ● MD (Max) 1.14mm ● OP 30.2±0.8mm

通用型微动开关 Z-20,Z-25 系列

Z-20GQ22 & Z-25GQ22

动作特性

● OF	3.89~6.11N	● OT (Min)	3.58mm
● RF (Min)	2.78N	● MD	0.05~0.2mm
● PT (Max)	1.3mm	● OP	33.4±1.2mm

Z-20GQ21 & Z-25GQ21

动作特性

● OF	3.89~6.11N	● OT (Min)	3.58mm
● RF (Min)	2.78N	● MD	0.05~0.2mm
● PT (Max)	1.3mm	● OP	33.4±1.2mm

Z-20GQ & Z-25GQ

动作特性

● OF	3.89~6.11N	● OT (Min)	5.56mm
● RF (Min)	2.78N	● MD	0.05~0.2mm
● PT (Max)	1.3mm	● OP	21.8±0.8mm