

**2100**

# 6½-Digit USB Digital Multimeter



The Model 2100 USB Digital Multimeter is the newest member of Keithley's family of high performance DMMs. Its high accuracy (38ppm), 6½-digit resolution is ideal for critical measurements. The Model 2100 features 11 measurement functions and 8 math functions to easily accommodate the most commonly measured parameters. All accessories, such as USB cable, probes, and software, are included with the Model 2100. With its unique combination of high precision and low total cost of ownership, the Model 2100 is an unbeatable value for R&D engineers, test engineers, scientists, and students making basic precision measurements on the bench and in system applications.

## High Precision, Low Cost

The Model 2100 provides stability, accuracy, and speed at a very low cost. It has 0.0038% 1-year range. At 6½ digits, the Model 2100 delivers 50 triggered rdgs/s into the USB remote interface. At the fast 4½ digit setting, it reads over 2000 rdgs/s into its 2000 reading internal buffer.

basic DC voltage accuracy on the 10V range and 0.013% 1-year basic resistance accuracy on the 10kΩ range. At 6½ digits, the Model 2100 delivers 50 triggered rdgs/s into the USB remote interface. At the fast 4½ digit setting, it reads over 2000 rdgs/s into its 2000 reading internal buffer.

The Model 2100 provides a wide number of measurement ranges and functions:

- DC voltage: 0.1V, 1V, 10V, 100V, and 1000V
- AC voltage: 0.1V, 1V, 10V, 100V, and 750V
- DC current: 10mA, 100mA, 1A, and 3A
- AC current: 1A and 3A
- Two- and four-wire resistance: 100Ω, 1kΩ, 10kΩ, 100kΩ, 1MΩ, 10MΩ, and 100MΩ
- Frequency: From 3Hz to 300kHz
- Period measurement
- Diode measurement
- Programmable A-D converter and filter settings for signal to noise optimization

Additionally, eight mathematical operations can be performed on measurement readings: RATIO, %, Min/Max, NULL, Limits, mX+b, dB, and dBm testing. Microsoft Office, Word, and Excel add-in tools allow remote storage and recall of the measured values from these applications. A graphing utility enables charting of measurements versus time for trending and noise observations.

The TMC compliant USB remote interface enables control from a PC for consistent test/calibration procedure execution and easy re-use of existing SCPI programs, including Agilent Model 34401A command emulation.

## Simple to Use

The Model 2100 can be setup quickly and is very easy to use. It has a high contrast front panel and keypad that are intuitive and user-friendly. An easy to read 5×7 dot matrix, vacuum fluorescent display (VFD) offers three-color annunciators so users can easily distinguish each function symbol by its color.

## Strength and Versatility

With its rugged construction and rubber bumpers, the Model 2100 has the durability to withstand bench, portable, or stacking applications. A sturdy carrying handle facilitates transportability.

- **High precision 6½-digit DMM for critical measurements at a 5½-digit price**
- **11 measurement functions cover most commonly measured parameters**
- **Fully specified accuracies on all functions for ISO-compliant results**
- **Included PC software utilities for graphing and data sharing in both Microsoft® Word and Excel**
- **Rugged construction for durability in bench/portable applications**
- **Selectable front/rear inputs facilitate bench or rack use**
- **Includes all accessories, such as startup software, USB cable, power cable, and safety test lead, for lowest total cost**
- **CE compliant and UL listed**
- **TMC compliant USB 2.0 interface for use with SCPI test programs**

**1.888.KEITHLEY** (U.S. only)**www.keithley.com****KEITHLEY**

A GREATER MEASURE OF CONFIDENCE

# 2100

# 6½-Digit USB Digital Multimeter

## Ordering Information

**2100/100** 6½-digit USB Digital Multimeter (100V)

**2100/120** 6½-digit USB Digital Multimeter (120V)

**2100/220** 6½-digit USB Digital Multimeter (220V)

**2100/230-240**  
6½-digit USB Digital Multimeter (230-240V)


## Accessories Supplied

Instruction manual on CD, Specifications, LabVIEW® Driver, Keithley I/O Layer, USB Cable, Power Cable, Safety Test Leads, KI-Tool, and KI-Link Add-in (Both Microsoft Word and Excel versions)

## Applications

The Model 2100 USB Digital Multimeter is ideal for applications in: electronic device, circuit, module, and product testing; low cost production testing of electrical and electronic components, sub-assemblies, and end products; and student lab assignments. Typical applications include:

- Test Engineers: Manual and semi-automatic electrical functional test
- Development Engineers: Electrical/electronic circuit and product validation
- Service/Calibration Technicians: Electronic product repair and calibration
- Research Scientists: Electrical and physics experiments testing
- Engineering Students: Electronic device and circuits experiment testing



## ACCESSORIES AVAILABLE

### RACK MOUNT KITS

|        |                                     |
|--------|-------------------------------------|
| 4299-3 | Single Rack Mount Kit               |
| 4299-4 | Dual Rack Mount Kit                 |
| 8605   | High Performance Modular Test Leads |
| 8606   | High Performance Modular Probe Kit  |

### SERVICES AVAILABLE

|                    |  |
|--------------------|--|
| 2100/120-3Y-EW     | 1 Year Factory Warranty extended to 3 years from date of shipment                    |
| C/2100/120-3Y-DATA | 3 (Z540-1 compliant) Calibrations within 3 years of purchase for Model 2100/120*     |
| C/2100/120-3Y-ISO  | 3 (ISO-17025 accredited) Calibrations within 3 years of purchase for Model 2100/120* |

\*Not available in all countries

## Startup Software, PC Utilities Included

The KI-Tool application provides charting and graphing capabilities without programming to simplify setup, checkout, and basic measurement applications requiring graphical data representation. Scale, offset, and level can be adjusted to fine tune images for visual evaluation of signal and noise elements over time. It also includes tabular data and SCPI command prompt windows for maximum flexibility. Data sets can also be saved to disk files.

The Microsoft Excel Add-In utility is also included and provides quick data import into a standard Microsoft Excel spreadsheet, including selectable graphing, instrument settings, and number of data points collected. Data can then be analyzed through standard or optional Microsoft Excel functions, including graphical, statistical, and trend charting. A version supporting Microsoft Word is also included for direct data import into reports.

1.888.KEITHLEY (U.S. only)

www.keithley.com

KEITHLEY

A GREATER MEASURE OF CONFIDENCE

Low cost 6½-digit DMM for portable, bench, and USB-based system applications

DIGITAL MULTIMETERS & SYSTEMS

## Specifications

### DC CHARACTERISTICS: Accuracy<sup>1</sup> ±(% of reading + % of range)

| Function   | Range       | Resolution | Input Resistance | 1 Year, 23°C ±5°C |
|------------|-------------|------------|------------------|-------------------|
| DC Voltage | 100.0000 mV | 0.1 μV     | >10 GΩ           | 0.0055 + 0.0040   |
|            | 1.000000 V  | 1.0 μV     | >10 GΩ           | 0.0045 + 0.0008   |
|            | 10.00000 V  | 10 μV      | >10 GΩ           | 0.0038 + 0.0006   |
|            | 100.0000 V  | 100 μV     | 10 MΩ            | 0.0050 + 0.0007   |
|            | 1000.000 V  | 1 mV       | 10 MΩ            | 0.0055 + 0.0010   |

| Function         | Range       | Resolution | Shunt Resistance | 1 Year, 23°C ±5°C |
|------------------|-------------|------------|------------------|-------------------|
| DCI (DC Current) | 10.00000 mA | 10 nA      | 5.1 Ω            | 0.055 + 0.025     |
|                  | 100.0000 mA | 100 nA     | 5.1 Ω            | 0.055 + 0.006     |
|                  | 1.000000 A  | 1 μA       | 0.1 Ω            | 0.120 + 0.015     |
|                  | 3.00000 A   | 10 μA      | 0.1 Ω            | 0.150 + 0.025     |

| Function                | Range       | Resolution      | Test Current | 1 Year, 23°C ±5°C |
|-------------------------|-------------|-----------------|--------------|-------------------|
| Resistance <sup>2</sup> | 100.0000 Ω  | 100 μΩ          | 1 mA         | 0.015 + 0.005     |
|                         | 1.000000 kΩ | 1 mΩ            | 1 mA         | 0.015 + 0.002     |
|                         | 10.00000 kΩ | 10 mΩ           | 100 μA       | 0.015 + 0.002     |
|                         | 100.0000 kΩ | 100 mΩ          | 10 μA        | 0.015 + 0.002     |
|                         | 1.000000 MΩ | 1 Ω             | 5 μA         | 0.017 + 0.002     |
|                         | 10.00000 MΩ | 10 Ω            | 500 nA       | 0.045 + 0.002     |
| 100.0000 MΩ             | 100 Ω       | 500 nA    10 MΩ | 1.00 + 0.020 |                   |
| Diode Test              | 1.0000 V    | 10 μV           | 1 mA         | 0.040 + 0.020     |
| Continuity              | 1000.00 Ω   | 10 mΩ           | 1 mA         | 0.024 + 0.030     |

### DC NOTES

- Specifications valid after two hour warm-up.
  - ADC set for continuous trigger operation.
  - Input bias current <30pA at 25°C.
  - Input protection 1000V all ranges (2W input).
  - Measurement rate set to 1 PLC.
- Specifications for 4W ohms mode. For 2W ohms, use zero null or subtract lead resistance from displayed reading.
  - Maximum lead resistance 10% of range per lead for 100Ω and 1kΩ ranges; add 1kΩ per lead for all other ranges.

### MEASUREMENT NOISE REJECTION DC (60Hz/50Hz)

| Rate  | Digits                        | CMRR <sup>1</sup> | NMRR <sup>2</sup> |
|-------|-------------------------------|-------------------|-------------------|
| 10PLC | 6 <sup>1</sup> / <sub>2</sub> | 140 dB            | 60 dB             |
| 1PLC  | 5 <sup>1</sup> / <sub>2</sub> | 140 dB            | 60 dB             |

- For 1kΩ unbalance in LO lead.
- For line frequency ±0.1%.

### TEMPERATURE (RTD)

| Range            | Resolution | 4-Wire Accuracy <sup>1</sup> , 1 Year |
|------------------|------------|---------------------------------------|
| -100°C to +100°C | 0.001°C    | ±0.1°C                                |
| -200°C to +630°C | 0.001°C    | ±0.2°C                                |

RTD TYPE: 100Ω platinum (PT100), D100, F100, PT385, or PT3916.

MAXIMUM LEAD RESISTANCE (each lead): 12Ω (to achieve rated accuracy).

SENSOR CURRENT: 1mA (pulsed).

- Excluding probe errors. 23°C ±5°C.

