



EFAP-S702

700W Output Power
 Supports Tylersburg Platform
 Single +12V Output Rail
 EPS2U Application for Rack Mount System
 Dimensions: 100(W) x 70(H) x 239.5(D) mm



INQUIRY

DownLoad

- 📄 [DRAWING](#)
- 📄 [CE](#) 📄 [FCC](#) 📄 [UL](#) 📄 [TUV](#) 📄 [CCC](#) 📄 [CB](#) 📄 [BSMI](#)

Features :

Universal Power Input
 Active Power Factor Correction
 Single +12V Output Rail
 Remote DC Sense on +5V and +3.3V
 Short Circuit Protection
 Over Current Protection
 Over Voltage Protection
 MTBF >100,000 Hours

General Specifications :

Input Range : 100 to 240 VAC, +/-10%
 Power Factor: , ≥0.97 minimum at full load
 Efficiency: ≥80%
 Hold up Time: 18mS minimum, at 80% of maximum load
 PSON (Remote ON/OFF): TTL compatible signal
 Power Good: 100 to 500 ms, TTL compatible signal
 Operating Temperature: 0 to 50 °C
 Operating Humidity: 20 to 90 %

Regulation, Ripple & Noise:

Output	+3.3V	+5V	+12V	-5V	-12V	+5Vsb
Load Regulation	± 5%	± 5%	± 5%		± 10%	± 5%
Cross Regulation	± 5%	± 5%	± 5%		± 10%	± 5%
Line Regulation	± 1%	± 1%	± 1%		± 1%	± 1%
Ripple & Noise	60mV	60mV	120mV		120mV	60mV

Input and Output Ratings:

Input			Output							
Voltage	Frequency	Current	Watt	Load	+3.3V	+5V	+12V	-5V	-12V	+5Vsb
100-240Vac	47-63Hz	10~5A	700W	Max. Load	26A	26A	58A		0.5A	3A
				Min. Load	0.5A	0.5A	1A		0.1A	0A

NOTE:

1. The +5 & +3.3 Volt combine total output shall not exceed 150W
2. The +5, +3.3 and +12 Volt combine total output shall not exceed 682W
3. Noise bandwidth is from DC to 20 MHz.

Agency Requirements :

Harmonic: Meet EN6 1000-3-2 standards
EMI/RFI: CE, FCC class B and CISPR class B
Safety: UL, cUL, CB, TUV, CCC