



# 228 Leakage Current Tester

## Model 228 Special Purpose AC/DC Milliammeter

Designed specifically to measure hazardous "Leakage Currents" or "Touch Currents" which may appear when a person touches the conductive surface of electrical or electronic equipment. The 228 is designed in accordance with IEC, ANSI and UL guidelines.

- True RMS Readings
- Reads in Measurement Indication Units (MIU) up to .005 MIU
- Output Allows Measurement of Peak Current in Non-Sinusoidal Wave Forms
- Let-Go, Reaction, and Burn Hazard Response Networks
- Detects dangerous AC & DC Leakage currents
- Includes Test Leads, Alligator Clips, Batteries and Manual



## Specifications

GENERAL	Reaction Response Network	Let-Go Response Network	Unweighted Burn Hazard Response Network
Equivalent network component values:	Complies with values specified in IEC 990 (excluding fuse)		
Equivalent measuring instrument load:	1 M $\Omega$ - 10pF	1 M $\Omega$ - 62 pF	1 M $\Omega$ - 1 pF
Ranges:	0.3, 1, 3, 10 M.I.U.	0.3, 1, 3, 10 M.I.U.	0-100 mA RMS
Current accuracy:	$\pm 2\%$ F.S. @ 60 Hz		
Meter measurement method:	True RMS		
Meter frequency response:	(Relative to ANSI C101-1992 or UL-1459 2nd edition)		
DC to 1 Hz	Pointer shall track within 5% of peak		
2Hz to 19Hz (Accuracy not supported)			
20 Hz to 200 KHz	$\pm 2\%$ F.S.	$\pm 2.5\%$ of F.S.	$\pm 2\%$ F.S.
200 KHz to 1 MHz	$\pm 2\%$ F.S.	$\pm 2.5\%$ F.S.	$\pm 5\%$ F.S.
Output sensitivity:	Full scale meter indication equals 1V RMS (Measured with a 1 M $\Omega$ , 12 pF load)		
Output accuracy:	$\pm 2\%$ of reading @ 60 Hz		
Output frequency response:	(Relative to ANSI C101-1992 or UL-1459 2nd edition)		
DC to 50Hz	$\pm 2\%$ of reading		
50 Hz to 100 KHz	$\pm 2.5\%$ of reading	+2% /-3% of reading	$\pm 2\%$ of reading
100 kHz to 1 MHz	$\pm 5\%$ of reading		
Voltmeter range:	0-300 V (AC or DC)		
Voltmeter accuracy: DC to 1 Hz	Pointer shall track within 5% of peak		
2Hz to 19Hz (Accuracy not supported)			
20 Hz to 1KHz	$\pm 3\%$ F.S. @ 60 Hz (Add $\pm 1\%$ for every additional 100Hz)		
Voltmeter frequency response:	DC to 1 KHz		
Power requirements:	(2) 9V (NEDA 1604A) batteries		
Physical:	7" x 5.25" x 3.125", 2-1/2 lbs (1.4kg), ABS plastic, fused input		
Environmental:	27°C $\pm 2^\circ$ C, 70% non condensing relative humidity. Outside this range derate by 10% per °C		
Maximum operating range:	0° to 40° C		

## Ordering Information

Specifications subject to change without notice.

Leakage Tester	Catalog No.	ACCESSORIES	Catalog No.
228 Leakage Current Tester	40027	Test Leads w/Screw-On Alligator Clips	00125
		Case, Black Padded Nylon Carrying	00834

Optional carrying case includes convenient storage pouch for test leads and accessories.

