



## 260-8Xi<sup>®</sup> & 260-8XPi<sup>®</sup> Analog VOM



**260-8Xi has all of the circuit protection features and advantages for which the 260 Series is famous...**

And even more features than its predecessors. The yellow case color for enhanced visibility and user safety awareness is the trademark of the 260-8Xi.

The durable ABS plastic case also provides high-impact resistance and increased drop protection in the toughest environments.

- Instant Trend Information for Quick Positive "Yes/No" Checks
- Zero RFI Emission
- Audible Continuity Check
- Resettable Overload Circuit Protection Relay Available on 260-8XPi
- 1.5 V and 9 V Batteries and Probe Test Leads With Alligator Clips
- Mirrored Scale for Parallax Reduction

Ordering Information	
VOM	Catalog Number
260-8Xi, Yellow	12395
260-8XPi, Protected Yellow	12396
Accessories	Catalog Number
Probe Leads w/ Screw-On Alligator Clip	00125
Probe Set, Replaceable Tip, Banana	07538
Lead Set, Alligator, Banana	07500
Clip Set, Alligator, Screw-On	00425
150-2 Amp Clamp Adapter, AC	00541
Case, Yellow Padded Polyester	00832
Case, Black Padded Polyester	00834
Case, Hard Leatherette Front Load	00805
Case, Molded Plastic	45028



## 260-8Xi<sup>®</sup> & 260-8XPi<sup>®</sup> Analog VOM

### Specifications

DC Voltage		
Ranges	Accuracy	Sensitivity
250mV, 2.5V, 10V, 25V, 50V, 250V, 500V, 1000V	2% of full scale	20K $\Omega$ per volt

AC Voltage		
Ranges	Accuracy	Sensitivity
2.5V, 10V, 25V, 50V, 250V, 500V, 1000V	3% of full scale	5K $\Omega$ per volt

Decibel	
5 Ranges	-20 to +50dB
Reference	0dB = 1mW into 600 $\Omega$

AC Current
Up to 250 AC amperes with AC Amp-Clamp Adapter Accessory # 00541

DC Current		
Ranges	Accuracy	Voltage Drop: (Nominal)
50 $\mu$ A, 1mA, 10mA, 100mA, 500mA, 10A	1.5% of full scale 50 $\mu$ A 2.0% of full scale, all others	250mV on 50 $\mu$ A/1mA; 255mV on 10mA/10A; 300mV on 100mA; 500mV on 500mA

Resistance		
Ranges	Accuracy	Maxium Indication
Rx1	2.5° of arc on Rx1	0 - 2K $\Omega$
Rx100	2.0° of arc on all others	0 - 200K $\Omega$
Rx10K	2.0° of arc on all others	0 - 20M $\Omega$

Batteries	1.5V D, 9V (Neda No.13F, 1604A)
Fuse	F1 1A, 250V, type 3AG, quick acting Littlefuse <sup>®</sup> Type 312001; F2 2A, 600V Littlefuse <sup>®</sup> Type BLS or 2A, 600V, Bussman <sup>®</sup> Type BBS
Dimensions	5-1/4" x 7" x 3-1/8", (13.34 x 7.78 x 7.94cm)
Weight	2 1/4 lbs. (1.02 Kg)
Rated Circuit-To Ground Voltage	1000V AC/DC Max

Specifications subject to change without notice.