

提夫自控技术（上海）有限公司



Electrical Data		
Nominal resistance	1/5/10	kOhm
Resistance tolerance	±20	%
Independent linearity	±1	% of meas. range
Electrical angle	340	°
Repeatability	max. 0.1	°
Temperature coefficient of the voltage divider	50	ppm/°C
Recommended wiper current	max. 1	µA
Max. wiper current in case of malfunction	10	mA
Power rating P	max. 0.5	W/40°C
Min. life (electrical)	10 Mio.	cycles
Mechanical Data		
Mechanical range	360	° (continuous)
Torque (IP54)	max. 3	Ncm
Min. life (mechanical)	10 Mio.	cycles
Max. permitted axial shaft load	100	N
Max. permitted radial shaft load	50	N
Operating temperature	-25 ... +85	°C
Storage temperature	-40 ... +105	°C
Protection class	IP67	
Standards		
Insulating resistance (500 VDC, 1bar, 2s)	10	GOhm
Dielectric strength (VAC, 50Hz, 1min, 1bar)	1	kV
Vibration (Amax = 0.75mm, f = 30 ... 2000 Hz)	10	g
Shock (half sine pulse, 7 ms)	50	g

PL360

Applications

- Joysticks / Master switches

Features

- Robust design
- Design flexibility
- 10 Mio. cycles
- Excellent linearity, up to ±0.25%
- Very good resolution, better 0,1°

Options

- Resistance tolerance ±10%
- Independent linearity ±0.25%
- Custom electrical angles and switch functions available
- Mechanical end stops
- Custom shaft design
- Custom housing design
- Customer specific wires

Subject to change
without notice
State: 27-Oct-2005