

Low ESR Cap.Compatible Positive Voltage Regulators

■GENERAL DESCRIPTION

The XC6206 series are highly precise, low power consumption, 3 terminal, positive voltage regulators manufactured using CMOS and laser trimming technologies. The series provides large currents with a significantly small dropout voltage.

The XC6206 consists of a current limiter circuit, a driver transistor, a precision reference voltage and an error correction circuit. The series is compatible with low ESR ceramic capacitors. The current limiter's foldback circuit operates as a short circuit protection as well as the output current limiter for the output pin.

Output voltages are internally by laser trimming technologies. It is selectable in 0.1V increments within a range of 1.2V to 5.0V.

SOT-23, SOT-89, TO-92 and USP-6B packages are available.


■APPLICATIONS

- Battery powered equipment
- Reference voltage sources
- Cameras, video cameras
- Portable AV systems
- Mobile phones
- Portable games
- Cordless phones,
wireless communication equipment

■FEATURES


Maximum Output Current	: 200mA (3.0V type)
Dropout Voltage	: 250mV @ 100mA (3.0V type)
Maximum Operating Voltage	: 6.0V
Output Voltage Range	: 1.2V ~ 5.0V (0.1V increments)
Highly Accurate	: $\pm 2\%$ @ $V_{OUT} \geq 1.5V$ $\pm 30mV$ @ $V_{OUT} < 1.5V$ ($\pm 1\%$ @ $V_{OUT} \geq 2.0V$)
Low Power Consumption	: $1.0\mu A$ (TYP.)
Low ESR Capacitor Protection	: Ceramic capacitor compatible Current Limit Circuit Built-in
Operating Ambient Temperature	: -40°C ~ +85°C
Packages	: SOT-23 SOT-89 TO-92 USP-6B
Environmentally Friendly	: EU RoHS Compliant, Pb Free

■TYPICAL APPLICATION CIRCUIT






■TYPICAL PERFORMANCE CHARACTERISTICS

XC6206P302



■ PIN CONFIGURATION



*The dissipation pad for the USP-6B package should be solder-plated in recommended mount pattern and metal masking so as to enhance mounting strength and heat release. If the pad needs to be connected to other pins, it should be connected to the pin number 4 (V_{IN}).

■ PIN ASSIGNMENT

PIN NUMBER				PIN NAME	FUNCTIONS
SOT-23	SOT-89	USP-6B	TO-92		
1	1	2	1	Vss	Ground
3	2	4	2	V_{IN}	Power Input
2	3	6	3	V_{OUT}	Output
-	-	1, 3, 5	-	NC	No Connection

■ PRODUCT CLASSIFICATION


● Ordering Information

XC6206P ①②③④⑤-⑥^(*)

DESIGNATOR	ITEM	SYMBOL	DESCRIPTION
①②	Output Voltage	12~50	e.g. V_{OUT} : 3.0V → ①=3, ②=0
③	Accuracy	2	$\pm 2\%$ ($V_{OUT} \geq 1.5V$), $\pm 30mV$ ($V_{OUT} < 1.5V$)
		1	$\pm 1\%$ ($V_{OUT} \geq 2.0V$)
④⑤-⑥	Packages (Order Unit)	MR	SOT-23 (3,000/Reel)
		MR-G	SOT-23 (3,000/Reel)
		PR	SOT-89 (1,000/Reel)
		PR-G	SOT-89 (1,000/Reel)
		DR	USP-6B (3,000/Reel)
		DR-G	USP-6B (3,000/Reel)
		TH	TO-92 (T type), Paper type (2,000/Tape)
		TH-G	TO-92 (T type), Paper type (2,000/Tape)
		TB	TO-92 (T type), Bag type (500/Bag)
		TB-G	TO-92 (T type), Bag type (500/Bag)

^(*) The “-G” suffix indicates that the products are Halogen and Antimony free as well as being fully RoHS compliant.

■ BLOCK DIAGRAM



*Diodes inside the circuit are an ESD protection diode and a parasitic diode.

■ ABSOLUTE MAXIMUM RATINGS

T_a=25°C

PARAMETER	SYMBOL	RATINGS	UNITS
Input Voltage	V _{IN}	7.0	V
Output Current	I _{OUT}	500 *	mA
Output Voltage	V _{OUT}	V _{SS} - 0.3 ~ V _{IN} + 0.3	V
Power Dissipation	SOT-23	250	mW
	SOT-89	500	
	USP-6B	100	
	TO-92	300	
Operating Ambient Temperature	T _{OPR}	- 40 ~ + 85	°C
Storage Temperature	T _{STG}	- 55 ~ + 125	°C

* I_{OUT}=P_d / (V_{IN}-V_{OUT})

■ ELECTRICAL CHARACTERISTICS

● XC6206P series

T_a=25 °C

PARAMETER	SYMBOL	CONDITIONS ^{(*)1}	MIN.	TYP.	MAX.	UNIT S	CIRCUIT
Output Voltage ^{(*)4}	V _{OUT(E)} ^{(*)3}	I _{OUT} =30mA	x 0.98	V _{OUT(T)} ^{(*)2}	x 1.02	V	①
Maximum Output Current	I _{OUTMAX}	-	E-2	-	-	mA	①
Load Regulation	ΔV _{OUT}	V _{OUT(T)>1.8V} : 1mA ≤ I _{OUT} ≤ 100mA V _{OUT(T)≤1.8V} : 1mA ≤ I _{OUT} ≤ 50mA	-	-	E-3	mV	①
Dropout Voltage ^{(*)5}	V _{dif1}	I _{OUT} =30mA	-	E-4		mV	①
	V _{dif2}	V _{OUT(T)>1.8V} : I _{OUT} =100mA V _{OUT(T)≤1.8V} : I _{OUT} =60mA	-	E-5		mV	
Supply Current	I _{DD}	V _{CE} =V _{IN}	-	1.0	3.0	μA	②
Line Regulation	ΔV _{OUT} ΔV _{IN} ·V _{OUT}	V _{OUT(T)<4.5V} : V _{OUT(T)+1.0V} ≤ V _{IN} ≤ 6.0V V _{OUT(T)≥4.5V} : 5.5V ≤ V _{IN} ≤ 6.0V I _{OUT} =30mA	-	0.05	0.25	%/V	①
Input Voltage	V _{IN}	-	1.8	-	6.0	V	-
Output Voltage Temperature Characteristics	ΔV _{OUT} ΔT _{opr} ·V _{OUT}	I _{OUT} =30mA -40 °C ≤ T _{opr} ≤ 85 °C	-	±100	-	ppm/ °C	①
Short Circuit Current	I _{short}	V _{IN} =V _{OUT} +1.5V, V _{OUT} =V _{SS}	-	E-6	-	mA	①

NOTE:

* 1 Unless otherwise stated, V_{IN} = V_{OUT(T)} + 1.0V

* 2 V_{OUT(T)} :Nominal voltage

* 3 V_{OUT(E)} :Effective output voltage (ie. The output voltage when "V_{OUT(T)+1.0V}" is provided at the V_{IN} pin while maintaining a certain I_{OUT} value.)

* 4 For output voltage accuracy, Please refer to E-1 table.

* 5 V_{dif} = V_{IN1} - V_{OUT1}

V_{OUT1} :A voltage equal to 98% of the output voltage whenever an amply stabilized {V_{OUT(T)} + 1.0V} is input with each I_{OUT}.

V_{IN1} :The input voltage when V_{OUT1} appears as input voltage is gradually decreased.


■ELECTRICAL CHARACTERISTICS (Continued)

●Electrical Characteristics Chart


PARAMETER NOMINAL VOLTAGE	E-1				E-2	E-3	E-4		E-5		E-6	
	OUTPUT VOLTAGE				MAX. OUTPUT CURRENT	LOAD REGULATIO N	DROPOUT VOLTAGE 1		DROPOUT VOLTAGE 2		SHORT CURRENT	
	2% ACCURACY		1% ACCURACY				Vdif1 (mV)		Vdif2 (mV)			
VOUT(T)	VOUT(E) (V)		VOUT(E) (V)		IOUTMAX (mA)	△VOUT (mV)	Vdif1 (mV)		Vdif2 (mV)		Ishort (mA)	
	MIN.	MAX.	MIN.	MAX.	MIN.	MAX.	TYP.	MAX.	TYP.	MAX.	TYP.	
1.2	1.170	1.230	Not Available		60	40	460	760	700	960	180	
1.3	1.270	1.330					400	650				
1.4	1.370	1.430					350	590		860		
1.5	1.470	1.530			80	45	300	510	450	810	155	
1.6	1.568	1.632					250	450				
1.7	1.666	1.734					200	410				
1.8	1.764	1.836					150	390				
1.9	1.862	1.938	Not Available		120	50	780		350	710	130	
2.0	1.960	2.040										
2.1	2.058	2.042										
2.2	2.156	2.244			150	55						
2.3	2.254	2.346				710		100	370	100		
2.4	2.352	2.448										
2.5	2.450	2.550										
2.6	2.548	2.652			200				60			
2.7	2.646	2.754				680		75	350			
2.8	2.744	2.856										
2.9	2.842	2.958										
3.0	2.940	3.060	2.970	3.030	250				70			
3.1	3.038	3.162	3.069	3.131		680						
3.2	3.136	3.264	3.168	3.232								
3.3	3.234	3.366	3.267	3.333								
3.4	3.332	3.468	3.366	3.434								
3.5	3.430	3.570	3.465	3.535								
3.6	3.528	3.672	3.564	3.636								
3.7	3.626	3.774	3.663	3.737	630	65	630		60	320	630	
3.8	3.724	3.876	3.762	3.838								
3.9	3.822	3.978	3.861	3.939								
4.0	3.920	4.080	3.960	4.040								
4.1	4.018	4.182	4.059	4.141								
4.2	4.116	4.284	4.158	4.242								
4.3	4.214	4.386	4.257	4.343								
4.4	4.312	4.488	4.356	4.444								
4.5	4.410	4.590	4.455	4.545								
4.6	4.508	4.692	4.554	4.646								
4.7	4.606	4.794	4.653	4.747	510	75	510		175	600	510	
4.8	4.704	4.896	4.752	4.848								
4.9	4.802	4.998	4.851	4.949								
5.0	4.900	5.100	4.950	5.050								

■ TEST CIRCUITS

Circuit ①






Circuit ②









■ TYPICAL PERFORMANCE CHARACTERISTICS

(1) Output Voltage vs. Output Current









(2) Current Limit






■ TYPICAL PERFORMANCE CHARACTERISTICS (Continued)

(3) Output Voltage vs. Input Voltage




(4) Dropout Voltage vs. Output Current




■ TYPICAL PERFORMANCE CHARACTERISTICS (Continued)

(5) Supply Current vs. Input Voltage




(6) Output Voltage vs. Ambient Temperature




■ TYPICAL PERFORMANCE CHARACTERISTICS (Continued)

(7) Output Voltage vs. Ambient Temperature





(8) Input Transient Response 1




■ TYPICAL PERFORMANCE CHARACTERISTICS (Continued)

(9) Input Transient Response 2









(10) Load Transient Response



■ TYPICAL PERFORMANCE CHARACTERISTICS (Continued)


(11) Ripple Rejection Rate



■PACKAGING INFORMATION


●SOT-23

Unit : mm




●SOT-89

Unit : mm




●USP-6B

Unit : mm




●TO-92

Unit : mm




■PACKAGING INFORMATION (Continued)

●USP-6B Reference Pattern Layout




●USP-6B Reference Metal Mask Design



■ MARKING RULE

● SOT-23, SOT-89



① represents product number

MARK		PRODUCT SERIES
6		XC6206P*****

② represents 3 pins regulator

MARK		PRODUCT SERIES
VOLTAGE=0.1 ~ 3.0V	VOLTAGE=3.1 ~ 6.0V	
5	6	XC6206P*****

③ represents output voltage

MARK	VOLTAGE (V)		MARK	OUTPUT VOLTAGE (V)		
0	-	3.1	-	F	1.6	4.6
1	-	3.2	-	H	1.7	4.7
2	-	3.3	-	K	1.8	4.8
3	-	3.4	-	L	1.9	4.9
4	-	3.5	-	M	2.0	5.0
5	-	3.6	-	N	2.1	-
6	-	3.7	-	P	2.2	-
7	-	3.8	-	R	2.3	-
8	-	3.9	-	S	2.4	-
9	-	4.0	-	T	2.5	-
A		4.1	-	U	2.6	-
B	1.2	4.2	-	V	2.7	-
C	1.3	4.3	-	X	2.8	-
D	1.4	4.4	-	Y	2.9	-
E	1.5	4.5	-	Z	3.0	-


④ represents production lot number

0 to 9, A to Z repeated. (G, I, J, O, Q, W excluded)

*No character inversion used.

■ MARKING RULE (Continued)

● USP-6B



①② represents product number

MARK		PRODUCT SERIES
①	②	
0	6	XC6206P***D*

③ represents 3 pins regulator

MARK	PRODUCT SERIES
P	XC6206P***D*

④⑤ represents output voltage


MARK		OUTPUT VOLTAGE(V)	PRODUCT SERIES
④	⑤		
3	3	3.3	XC6206P33*D*
5	0	5.0	XC6206P50*D*

⑥ represents production lot number

0 to 9, A to Z repeated. (G, I, J, O, Q, W excluded)

*No character inversion used.

● TO-92



① represents type of regulator

MARK	PRODUCT SERIES
P	XC6206P*****

②③ represents output voltage

MARK		VOLTAGE (V)	PRODUCT SERIES
②	③		
3	3	3.3	XC6206P33***
5	0	5	XC6206P50***

④ represents output voltage accuracy

MARK	OUTPUT VOLTAGE ACCURACY	PRODUCT SERIES
1	±1%	XC6206P**1**
2	±2%	XC6206P**2**

⑤ represents least significant digit of the production year

MARK	PRODUCTION YEAR
3	2003
4	2004

⑥ represents production lot number

0 to 9, A to Z repeated. (G, I, J, O, Q, W excluded)

*No character inversion used.