

Infrared Gas Monitors  
Guardian Range

# GUARDIAN PLUS

FOR CO<sub>2</sub> OR CH<sub>4</sub>




The Guardian range of infrared gas monitors offers near-analyser quality continuous sampling, measurement and display of target gas concentrations at a very attractive cost.

The 'Guardian Plus' range provides high accuracy detection and measurement of either CO<sub>2</sub> or CH<sub>4</sub> gases, where detection level ranges of between 0-3000ppm and 0-100% by volume are required.


Suitable for a wide variety of applications these wall-mounted monitors can detect gases from sampling points up to 30 metres away, using the integral sampling system.

The proven reputation of these instruments for reliability, accuracy and long-term stability with low maintenance requirements can be attributed to our proprietary dual-wavelength infrared sensor technology and over thirty years of sensor design and manufacturing experience.


Our Guardian instruments feature a four-digit LCD and alarm set-point controls and are housed in a tough plastic enclosure that has an IP54 rating against the ingress of particulates and water.



GAS SENSORS



ANALYTICAL INSTRUMENTS



LASERS AND ELECTRO-OPTICS



QUANTUM DIVISION



 EDINBURGH  
INSTRUMENTS




MODEL	Gas	Accuracy*	Stability	Repeatability @ zero	Repeatability @ span
Guardian Plus 0-3000ppm	CO <sub>2</sub>	+/- 2.5% of range	+/- 2% of range over 12 months	+/- 0.3%	+/- 2%
Guardian Plus 0-1%	CO <sub>2</sub>	+/- 2.5% of range	+/- 2% of range over 12 months	+/- 0.3%	+/- 2%
Guardian Plus 0-3%	CO <sub>2</sub>	+/- 2.5% of range	+/- 2% of range over 12 months	+/- 0.3%	+/- 2%
Guardian Plus 0-5%	CO <sub>2</sub>	+/- 2.5% of range	+/- 2% of range over 12 months	+/- 0.3%	+/- 2%
Guardian Plus 0-10%	CO <sub>2</sub>	+/- 2.5% of range	+/- 2% of range over 12 months	+/- 0.3%	+/- 2%
Guardian Plus 0-30%	CO <sub>2</sub>	+/- 2.5% of range	+/- 2% of range over 12 months	+/- 0.3%	+/- 2%
Guardian Plus 0-100%	CO <sub>2</sub>	+/- 2.5% of range	+/- 2% of range over 12 months	+/- 0.3%	+/- 2%
*Guardian Plus 0-1%	CH <sub>4</sub>	+/- 4% of range	+/- 3% of range over 12 months	+/- 0.15%	+/- 3%
*Guardian Plus 0-5%	CH <sub>4</sub>	+/- 3% of range	+/- 3% of range over 12 months	+/- 0.3%	+/- 2.5%
Guardian Plus 0-10%	CH <sub>4</sub>	+/- 2.5% of range	+/- 2% of range over 12 months	+/- 0.3%	+/- 2%
Guardian Plus 0-30%	CH <sub>4</sub>	+/- 2.5% of range	+/- 2% of range over 12 months	+/- 0.3%	+/- 2%
Guardian Plus 0-100%	CH <sub>4</sub>	+/- 2.5% of range	+/- 2% of range over 12 months	+/- 0.3%	+/- 2%
<b>RESPONSE TIME:</b>	T <sub>90</sub> = 30 seconds				
<b>OPERATING TEMPERATURE:</b>	0-40°C				
<b>WARM-UP TIME:</b>	3 minutes (initial), 40 minutes (full specification)				
<b>HUMIDITY:</b>	Measurements are unaffected by 0-99% relative humidity, non-condensing				
<b>CONTROLS FITTED:</b>	Zero and span adjustment potentiometers Setpoint 1 and setpoint 2 adjustment View setpoint 1 button, view setpoint 2 button Indicator LED and display test button				
<b>BITSWITCH PARAMETERS:</b>	Analogue (current) output: 0 - 20mA or 4 - 20mA Linear or non-linear output Alarm settings: alarm 1 high/low, alarm 2 high/low, alarm 1 normal/latch, alarm 2 normal/latch Buzzer sounds on both alarms or only on alarm 2 Low flow warning (flashing lamp) or low flow alarm (audible alarm, LCD displays 'ERR', flashing lamp, etc)				
<b>VISUAL DISPLAY:</b>	Four-digit LCD Alarm 1 LED, alarm 2 LED Fault LED Low flow/flow fail LED				
<b>RELAY CONTACTS:</b>	Volt-free changeover contacts Resistive load @ 24V DC = 8A Resistive load @ 250V AC = 8A				
<b>PUMP CHARACTERISTICS:</b>	Typical flow rate = 1 litre/minute Maximum sampling distance = 30 metres				
<b>POWER REQUIREMENTS:</b>	88V - 138V AC or 172V - 276V AC (switch selectable)				
<b>POWER CONSUMPTION:</b>	13 W (typical)				
<b>WEIGHT:</b>	2.5Kg				
<b>DIMENSIONS:</b>	267 x 258 x 148mm				
<b>ENCLOSURE:</b>	IP54 rated				
<b>ELECTRICAL CONFORMITY:</b>	CE marked				
	(*stated accuracy includes calibration gas tolerance of +/- 1%)				

#### OTHER GUARDIAN MODELS AVAILABLE:

Guardian SP:	Measurement of ppm level CO <sub>2</sub> and N <sub>2</sub> O; measurement of % level CO
Guardian FR:	Measurement of refrigerants (HCFC / HFC/ Freons) at ppm level

\*\*Guardian Plus instruments are not certifiable for use where risk of fire or explosion exists. During operation prolonged exposure to high levels of flammable gases may lead to the creation of an explosive mixture within the Guardian plus enclosure. Additional measures must be taken by the user to prevent this hazard occurring.

Edinburgh Instruments Ltd  
2 Bain Square,  
Kirkton Campus,  
Livingston EH54 7DQ



www.edinst.com  
sales@edinst.com  
Tel: 01506 425300