

FEATURES

- Open VPX VITA 62 compliant
- Wide input range
- High power DC output
- Efficiency of 90% typical
- Conduction cooled at card edge

**6U Open VPX VITA 62 High Power 12 VDC Power Supply with 3.3 V Auxiliary**

The Behlman VPXtra™1000CD series COTS DC to DC power supply is a rugged, highly reliable, conduction cooled, switch mode unit built for high-end industrial and military applications. The VPXtra™1000CD is a VITA 62, Open VPX compliant, 6U, power supply that delivers 1000 Watts of DC power with a 3.3 volt AUX. 12 volt output can be paralleled for higher power and redundancy. The VPXtra™1000CD can accept a 28 VDC input, IAW MIL-STD-704, and can supply a high power DC output at various power levels dependent on cooling capability.

The VPXtra™1000CD power supply has no minimum load requirement and has overvoltage and short circuit protection as well as over current and thermal protection. The power supply is designed to support the rigors of mission critical airborne, shipboard, vehicle and mobile applications.

Designed and manufactured with Xtra-Cooling™ technology, Xtra-Reliable™ design and Xtra-Rugged™ construction makes the Behlman VPXtra™ 1000CD your best choice.

INPUT

Voltage: 18 to 36 VDC

OUTPUT

Power: 1000 Watts
Voltage/Current: 12 VDC @ 80 Amps
Auxiliary: 3.3 VDC @ 15 Amps
Line Regulation: 0.5% maximum
Load Regulation: 1.0% maximum (0-100%)
PARD-Ripple & Noise: 50mV p-p (0-20 MHz)
Efficiency: 90% typical

PROTECTIVE CIRCUITS

Over Voltage: 120% typical
Over Current: 120% typical
Over Temp Warning
Over Temp

CONTROLS (+12 VDC IAW VITA 62)

Inhibit: Output Off- active low
Enable: Input On- active low

INDICATORS (Four LED's for the following):

Input OK: Green
Output Enable: Green
Output Fault: Red
Over Temp: Red

GENERAL CHARACTERISTICS**Isolation:**

Input to Output: 500 VDC
Input to Case: 500 VDC
Output to Case: 500 VDC

ENVIRONMENTAL (Temperature at card edge)

Temperature: (IAW VITA 47)
Operating: (CC3) -40°C to +70°C
Storage: (C2) -40°C to +85°C

MECHANICAL (1.0 inch pitch)

Dimensions: 9.19"L x 6.64"W x .97"H
Weight: Approximately 4.0 lbs
Input Connector: P0- IAW O&C drawing 24148
Output Connector: P1- IAW O&C drawing 24148

Designed to meet the following MIL Standards

Shock: MIL-STD-810
Vibration: MIL-STD-810
Humidity: MIL-STD-810
EMI: MIL-STD-461

VPXtra™ is a trademark of Behlman Electronics.
 VPX is a trademark of VITA.

