



Specifications : Bulk density as low as 0.2
 Detection sensitivity : 133mm
 Length : 133mm
 Mounting plug: G 3/4
 Cable inlet : JIS F20a(G 3/4)
 Power supply : 180 to 264 V AC 50/60Hz

23	Ground terminal	1	Brass (C3604BD)
22	Sensitivity setting switch	1	
21	Fail-safe mode setting switch	1	
20	Alarm indicator	1	
19	Test point 1	1	
18	Test point 2	1	
17	Sensitivity setting volume	1	
16	Test point 3	1	
15	Terminals	1	
14	Plug	1	304 stainless steel
13	Detection rod	1	304 stainless steel
12	Cap	1	304 stainless steel
11	Extension pipe	1	304 stainless steel
10	Gasket	1	Silicone
9	Screw	1	Aluminium Alloy Die Casting
8	Nut	1	Brass (C3604BD)
7	Washer	1	Brass (C3710P)
6	Packing	1	Acrylonitrile-Butadiene Rubber
5	Cable gland	1	Brass (C3604BD)
4	Housing	1	Aluminium Alloy Die Casting
3	Cover gasket	1	Chloroprene Rubber
2	Cover bolt	2	Stainless steel
1	Cover	1	Acrylonitrile-Butadiene Styrene
P.No.	Name	Qty.	Material

△		DATE JUN.28, 1993	DR. BY	TITLE	
△		SCALE 1:2.5	CH. BY	OUTLINE DRAWING OF	
△		UNITS mm	APP. BY	MODEL VM 32	
REV	DATE	DESCRIPTION	BY	APP. BY	SHEET NO.
		REVISIONS			DRAWING NO. CA 107004

NOHKEN INC
OSAKA, JAPAN

