

Waterproof ExStik® pH Meter

Features flat surface electrode, RENEW and CALibration alerts, memory, and bargraph



Patent Pending

The **ONLY** Stick style pH Meter with a:

- ✓ **Flat Surface Electrode** measures pH in liquids, semi-solids, and solids. No more electrode breakage or clogged junctions.
- ✓ **RENEW** indicator tells you it's time to replace your electrode. Eliminates guesswork.
- ✓ **CAL** alert tells you it's time to recalibrate. Ensures accuracy.
- ✓ **Memory** records and recalls 15 sequentially tagged readings. Allows detection of changes over time.
- ✓ **Analog bargraph** displayed on LCD. Shows trends in acidity or alkalinity



Flat Surface Electrodes work in liquids, semi-solids and solids

More Features/Functions:

- 1, 2 or 3 point calibration automatically recognizes buffer solutions
- Automatic Temperature Compensation
- Simultaneous display of pH and Temperature
- Waterproof to IP57 standard
- Display indicates when the reading is stabilized
- Data Hold, Auto power off and low battery indication
- Waterproof design floats in water and protects the meter in wet environment
- Interchangeable probes available for Chlorine & ORP
- Optional weighted base (EX006) holds plastic cup and ExStik® meter
- Complete with flat surface pH electrode, protective sensor cap, sample cup with cap, four 3V CR-2032 button batteries, and 48" (1.2m) neckstrap

Ordering Information:

PH100Waterproof ExStik® pH Meter
PH105Spare pH ExStik® Electrode Module
EX006Weighted base with 5 solution cups
PH103Tripak buffers (6ea - 4, 7, 10pH & 2 Rinse solutions)
EX007Spare sample solution cups (24pk)
CA903Carrying case for ExStik™ kit
RE305Spare Probe, ORP
CL205Spare Probe, Chlorine
PH115Spare Probe, pH, Refillable Reference
PH4-PpH 4 Buffer Solution (2 Bottles, 1 Pint (475 mL) Each
PH7-PpH 7 Buffer Solution (2 Bottles, 1 Pint (475 mL) Each
PH10-PpH 10 Buffer Solution (2 Bottles, 1 Pint (475 mL) Each
CA895Carrying Case, Small with Belt Loop
EX800Carrying Case, Small with Belt Loop
EX900ExStik 4-in-1 Kit (Chlorine, pH, ORP, Temp)
DO610ExStik DO/pH/Conductivity Kit

Specifications	
pH:	0.00 to 14.00pH
Temperature:	23 to 194°F (-5 to 90°C)
Resolution:	0.01pH, 0.1°
Accuracy:	±0.01pH, ±1.8°F/±1°C
Power:	four LR44 button batteries
Dimensions:	1.4x6.8x1.6" (35.6x172.7x40.6mm)
Weight:	3.8oz (110g)

EXTECH INSTRUMENTS CORPORATION
285 Bear Hill Road, Waltham, MA 02451-1064, U.S.A.
Phone: 781-890-7440 • FAX 781-890-7864

ISO 9001:2000 CERTIFIED

"Make mine an Extech!"
www.extech.com



02/16/06 - R5