

典型应用: 废水 | 源水 | 游泳池 和 Spa

	变送器			控制器	
	TX10	TX100	TX20	TX3000	TX2000 (RS)
					
测量范围	-2.00...+16.00pH -1999mV...+1999mV	0.00...14.00pH -1999mV...+1999mV	-2.00...+16.00pH -1999mV...+1999mV	-2.00...+16.00pH -1999mV...+1999mV	-2.00...+16.00pH -1999mV...+1999mV
温度补偿范围	ATC -10...+120°C	ATC -20...+110°C	ATC -10...+120°C	ATC -30...+130°C	ATC -30...+130°C
分辨率	0.01pH 1mV	0.01pH 1mV	0.01pH 1mV	0.01pH 1mV	0.01pH 1mV
4-20mA 输出	1	1		2	2 (1)
MODBUS 输出					0 (1)
报警/ 控制 RELAYS			✓	✓	✓
防水 RESISTANT		✓		✓	✓
盘装	✓	✓	✓	✓	✓
墙装		✓		✓	✓
图形显示					✓
尺寸	1/8 DIN: 3.78" (96 mm) x 1.89" (48 mm)	1/4 DIN: 3.9" (99 mm) x 3.9" (99 mm)	1/8 DIN: 3.78" (96 mm) x 1.89" (48 mm)	1/2 DIN: 5.7" (145 mm) x 5.7" (145 mm)	1/4 DIN: 3.78" (96 mm) x 3.78" (96 mm)
DEPTH	3.54" (90 mm)	2.9" (74 mm)	3.54" (90 mm)	5.20" (132 mm)	4.5" (114 mm)
POWER	100-240 VAC 50/60 Hz	12-24 VDC (Loop)	100-240 VAC 50/60 Hz	100-240 VAC 50/60 Hz	100-240 VAC 50/60 Hz