

典型应用：废水 | 冷却塔 | 锅炉 | 湿法除尘

	TRANSMITTERS				CONTROLLERS		
	CONTACTING	TOROIDAL			CONTACTING	BOILER	
	CX10 	CX100 	TCSMA 	TCSTX 	CX20 	CX2000 (RS) 	CX3000 
参数	电导率 电阻率	电导率	无电极法 电导率	无电极法 电导率	电导率 电阻率	电导率 电阻率	电导率 电阻率 盐度
温度	ATC -10 ... +120°C	ATC -20 ... +110°C	ATC -20 ... +60°C	ATC -20 ... +60°C	ATC -10 ... +120°C	ATC -30 ... +130°C	ATC -30 ... +200°C
范围	4 (0...19.99mS)	6 (0...199.9mS)	5 (0...2000mS)	5 (0...2000mS)	4 (0...19.99mS)	5 (0...200mS)	6 (0...200mS)
最大分辨率	0.001uS/cm	0.01uS/cm	0.1uS/cm	0.1uS/cm	0.001uS/cm	0.01uS/cm	0.001uS/cm
4-20mA 输出	1	1	1	1		2 (1)	2
MODBUS 输出						0 (1)	
报警/控制 继电器					✓	✓	✓
防水		✓	✓	✓		✓	✓
图形显示			盲			✓	
盘装	✓	✓	✓	✓	✓	✓	✓
墙装		✓	✓	✓		✓	✓
尺寸	1/8 DIN: 3.78" (96 mm) x 1.89" (48 mm)	1/4 DIN: 3.9" (99 mm) x 3.9" (99 mm)	4.4" (112 mm) x 4.4" (112 mm)	4.4" (112 mm) x 4.4" (112 mm)	1/8 DIN: 3.78" (96 mm) x 1.89" (48 mm)	1/4 DIN: 3.78" (96 mm) x 3.78" (96 mm)	1/2 DIN: 5.7" (145 mm) x 5.7" (145 mm)
深度	3.54" (90 mm)	2.9" (74 mm)	3.5" (90 mm)	3.5" (90 mm)	3.54" (90 mm)	5.20" (132 mm)	4.5" (114 mm)
电源	100-240 VAC	12-24 VDC (回路)	16-35 VDC (回路)	16-35 VDC (回路)	100-240 VAC	100-240 VAC	100-240 VAC