



## 工作压力 operating pressure:

0.6, 1.6, 2.5, 4.0, 6.4, 10.0MPa

## 工作温度 operating temperature: -50~450℃

## 测量范围 measuring range L:

(两法兰间中心距center length) 300、500、800、1100、1400、1700、2000mm。

锅炉水位计boiler level gauge: 300、400、440mm。

特殊规格请用户注明。Special on request.

## 过程连接 process connection:

DN20(或DN25、DN40)凸面(或平面), 法兰标准

HG20592~20635-97, 其它法兰标准请用户注明。

Convex flange as above, other on request.

## 伴热蒸汽夹套 steam heating jacket:

工作压力operating pressure 1.0MPa,

接管尺寸joint G1/2" 外螺纹outer thread。

## 伴热循环水夹套 cycling water jacket:

工作压力operating pressure 1.0MPa,

接管尺寸joint G3/4" 外螺纹outer thread。

## 电伴热 electrical heating jacket: 采用自限温度伴热带

及防爆温度监控器, 防爆等级Eex ed II CT6

## 钢珠自动封闭压力 steel ball automatically sealing

pressure: ≥0.2MPa

## 型号规格 MODEL AND SPEC

UGS-	彩色石英玻璃液位计 color quartz glass liquid level gauge		
A	标准型, 无盲区, 阀门带安全装置, 带排污阀, 温度-50~450℃ trandard type with safety unit and drain valve, no blind area		基本型式 basic type
B	普通型, 温度-50~450℃ common type		
C	防腐型, 不锈钢内衬PP材质, 温度≤80℃ anti-corrosive type, stainless steel with PP lining		
D	防腐型, 不锈钢内衬PTFE材质, 温度≤200℃ anti-corrosive type, stainless steel with PTFE lining		
G	大口径玻璃液位计 heavy caliber glass liquid level gauge		
	1	碳钢 carbon steel	材质 material
	2	不锈钢 1Cr18Ni9Ti, 304SS, 316L stainless steel	
	-	06 0.6MPa	工作压力 operating pressure
		16 1.6MPa	
		25 2.5MPa	
		40 4.0MPa	
		64 6.4MPa	
		100 10.0MPa	
	-	20 DN20	法兰通径 nominal diameter of flange
		25 DN25	
		40 DN40	
		RF 凸面 convex	法兰密封面 sealing face
		FF 平面 plane	
	-	300 300mm	测量范围 measuring range
		500 500mm	
		800 800mm	
		1100 1100mm	
		1400 1400mm	
		1700 1700mm	
		2000 2000mm	
		□ 特殊规格填数字 numeral for special, 单位 mm	
	J1	蒸汽加热夹套 with steam heating jacket	伴热选项 optional heating jacket
	J2	循环水加热夹套 with cycling water heating jacket	
	J4	电伴热 with electrical heating jacket	