

SPECIFICATIONS:

POWER RATING:

2 WATTS MAX. @ 40°C.
2.4 WATTS MAX. @ 25°C.

CONNECTOR: N-TYPE FEMALE

FREQUENCY RANGE & VSWR:

DC TO 1 GHz AT 1.10:1 MAX.
1 GHz TO 6 GHz AT 1.25:1 MAX.

IMPEDANCE: 50 OHMS NOMINAL

AMBIENT TEMPERATURE: RANGE: -40°C TO +40°C

OPERATING POSITION: ANY


COOLANT: DRY (CONVECTION COOLED)

FINISH: SILVER OR TRI-ALLOY PLATED

NOMINAL SIZE: APPROX. 1.50" L X .700" DIA.

WEIGHT: APPROX. 1.5 oz. (42 g)

REVISIONS		DWG. NO.	2-T-FN	SHEET	REV
				1	A
ZONE	REV	DESCRIPTION	DATE	APPROVED	
	A	ECN #0049/CHNG LABEL, FINISH	3-27-96	<i>MRE</i>	



UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCES ARE:

MILLIMETERS
.X= ±.4
.XX= ±.12

FRACTIONS DECIMALS ANGLES
± 1/64 .XX= ±.010 ± 30'
.XXX= ±.005

DO NOT SCALE DRAWING

THIS DRAWING IS THE PROPERTY OF THE BIRD ELECTRONIC CORPORATION. THE DESIGNS AND SPECIFICATIONS DISCLOSED HEREON ARE PROPRIETARY AND SHALL NOT BE REPRODUCED, NOR COPIED, NOR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT THEIR EXPRESS WRITTEN CONSENT.



BIRD Electronic Corporation
Cleveland (Solon) Ohio USA

MATERIAL	APPROVALS	DATE	TITLE			
	DRAWN D.M.RINK	5-16-03	FINAL ASS'Y/TERMINATION N-TYPE FEMALE, 2W			
FINISH	CHECKED		SIZE	FSCM NO.	DWG. NO.	REV
	APPROVED <i>MRE</i>	6-6-03	A	70998	2-T-FN	A
		AUTOCAD	SCALE	COMM CODE	SHEET	
			1:1	LD1	1 OF 1	