



OPTIMA HX™ MINI SERIES // HIGH PERFORMANCE UV SYSTEMS

Efficient and cost effective, the Optima HX mini provides proven performance and technology in numerous applications such as Food & Beverage, Life Sciences and Microelectronics.



MODEL SHOWN: Optima HX Mini 02 BDM U // **INDUSTRIES:** Food & Beverage, Life Sciences, Microelectronics // **FLOWRATES:** 9-33GPM @ 94%UVT, 10-39GPM @ 99%UVT // **APPLICATIONS:** Disinfection, Ozone Destruction // **DESIGN CAPABILITIES:** Custom Configurations

OPTIMA HX MINI SERIES

The Optima HX™ mini series was designed with a sophisticated sizing program, combining Multiple Source Summation (MPSS) and Computational Fluid Dynamics (CFD), critical in calculating fluency rates, flow patterns and velocity distribution.

The series consists of 316L stainless steel treatment chamber and a stainless steel control panel in one integral unit for models with reactors up to 6" in diameter. All models have a standard UL TYPE - 1 painted carbon steel control cabinet.

With low-pressure high-output lamp (LPHO) technology, the HX lamp provides increased process performance and extended lamp life, while the systems compact size allows for a smaller footprint, maximizing installations flexibility. Single-ended (SE) HX lamps allow quick change-outs without tools. All Optima HX mini systems are cULus certified.

Utilized for ozone destruction and disinfection, the Optima HX™ mini is not only cost effective, but proves to be a reliable, innovative and environmentally smart alternative.

UV Technology

Aquafine ultraviolet (UV) systems are engineered to focus the power of UV light, utilizing specially designed Aquafine Colorguard™ UV technology is used throughout the world, in a wide array of applications, as a environmentally responsible way to disinfect and safeguard water against harmful microorganisms.

Safe & Effective

UV disinfection is a chemical-free process that adds nothing to the water except UV light. It provides rapid, effective inactivation of microorganisms through a physical process. When bacteria, viruses and protozoa are exposed to the germicidal wavelengths of UV light, they are rendered incapable of reproducing and infecting. No carcinogenic disinfection by-products are created, and no transportation, storage or handling of toxic or corrosive chemicals is necessary.

Guaranteed Performance and Support Services

All of our systems come with a lifetime disinfection guarantee. Customer support is available from our Authorized Distributor Network and from our 24/7 Technical Service Group.

For questions regarding your application needs, please contact your local Authorized Distributor or Aquafine for more information.

OPTIMA HX™ MINI SERIES // HIGH PERFORMANCE UV SYSTEMS

Model: Optima HX mini	HX01 BDM U	HX02 BDM U	HX02 CDM U	HX03 CDM U
MAXIMUM FLOW RATE				
DISINFECTION (@94% UVT) GPM (M ³ /HR)*	9 (2.0)	16 (3.6)	24 (5.4)	33 (7.5)
DISINFECTION (@99% UVT) GPM (M ³ /HR)*	10 (2.2)	17 (3.9)	28 (6.3)	39 (8.9)
NUMBER OF UV LAMPS (HX SE)	1	2	2	3
ELECTRICAL REQUIREMENTS				
ELECTRICAL SUPPLY	120/240V/50-60Hz, SINGLE PHASE, 2 W + GND			
OPERATING POWER	50	100	100	150
BALLAST TYPE	ELECTRONIC			
CONTROLLER/DETECTOR				
UV G400 SERIES	N/A			
UV TEMP. & MONITORING SYSTEM	OPTIONAL			
LAMP STATUS INDICATOR	STANDARD			
LAMP OUT ALERT (LOA)	OPTIONAL			
RUNNING TIME METER	STANDARD			
HAND/OFF/AUTO (HOA)	OPTIONAL			
4-20mA OUTPUT SIGNAL	OPTIONAL			
CONTROL CABINET				
CC SYSTEM RATING	CARBON STEEL - UL TYPE 1, STAINLESS STEEL - UL TYPE 3R OR NEMA 4X			
MATERIALS OF CONST. STD / "U"	CARBON STEEL (304 STAINLESS STEEL OPTIONAL)			
TREATMENT CHAMBER				
MATERIALS OF CONSTRUCTION	316L STAINLESS STEEL			
INTERNAL SURFACE FINISH	Ra 32 (Ra 15 OPTIONAL)			
OPERATING TEMPERATURE °F (°C)	Water: 41° - 104° (5° - 40°) Ambient Air: 34° - 104° (1° - 40°)			
MAX. OPERATING PRESSURE PSI (BAR)	150 (10)			
INLET/OUTLET FLANGE INCHES (MM)	1 (25)	2 (50)		
INLET/OUTLET FLANGE TYPE	FNPT (FLANGED OR SANITARY OPTIONAL)			
HOT WATER SANITIZATION °F (°C)	170° (77°) AVAILABLE WITH S.S. COMP. NUTS ONLY			
DIMENSIONS - FOR REFERENCE ONLY				
STANDARD CC DIMENSIONS - CARBON STEEL INCHES (MM) L X W X H	16 X 7 X 18 (406 X 178 X 457)			
STANDARD TC DIMENSIONS - STAINLESS STEEL INCHES (MM) L X W X H	24 X 7 X 11 (609 X 178 X 279)	24 X 9 X 19 (609 X 229 X 483)		

* Dose Level: 30 mJ/cm² after 9,000 hours of operation.



North America & International
29010 Ave Paine, Valencia, CA 91355
P +1 661 257 4770 F +1 661 257 2489
sales@aquafineuv.com | www.aquafineuv.com

Europe
Ramskamp 77-85 D-25337 Elmshorn, Germany
P +49 4121 57806 13 F +49 4121 57806 30
saleseu@aquafineuv.com | www.aquafineuv.com



Aquafine is an ISO 9001:2008 certified company.