## **Multi Gas Clip**

The first portable multi gas detector with a battery life of months instead of hours.



- 2-month battery life on a single charge
- Compact and lightweight
- 6-month calibration cycle
- Low maintenance cost
- Simple to use
- 100% quality control testing
- LEL sensor (IR) does not require oxygen



Portable gas detectors you can count on.



IR DATA LINK

## MGC DOCK

Part # Description

MGC 4 Gas Monitor with infrared sensor

MGC-P 4 Gas Monitor with pellistor sensor

MGC-DOCK 4 bay calibration and bump test station

GCT-IR-LINK GCT IR communication module w/ USB cable

MGC Confined Space Kit (monitor and gas sold separately)

Please contact Gas Clip Technologies for additional spares, accessories and gas.

**Distributed By:** 

## **Specifications**

**Size** 4.7 x 2.4 x 1.2 in. (118.6 x 61.6 x 31.7 mm.)

**Weight** 7.7 oz. (240 g)

**Temperature** -4 to +122°F (-20 to +50°C)

**Humidity** 5% to 95% RH (non-condensing)

Battery Life

IR
60 days continuous
Pellistor
25 hours (typical)

Charge Time 4-6 hours

Alarms Visual, Vibrating, Audible (minimum 95dB) Low, High, STEL, TWA and OL (Over Limit)

**LEDs** 4 red alarm bar LEDs

Yellow backlight (activated on button press)
Red backlight (activated on alarm condition)
Yellow Maintenance Notification LED

Alphanumeric Liquid Crystal Display

Logs 25 Bump test 25 Events

25 Events 25 Calibrations

Continuous 1 Second Data Logging (>2mth typical capacity)

**Tests** Full function self-test upon activation

Sensors, battery and circuitry continuous

Ingress Protection IP66/67

Certifications and Approvals

**Display** 



CAN/CSA C22.2 No.157 and C22.2 152 ANS/UL-913 and ANSI/ISA – S12.13 Part 1 CSA: Class 1, Division 1, Group A, B, C, and D



ATEX: Pending
IECEx: Ex ia IIC T4 Ga

Warranty Full 2 years

**Gases**  $H_2S$  0 – 100 PPM

CO 0-500 PPM Combustible 0-100 %LEL  $O_2$  0-30 %

**Sensor Type** *H*<sub>2</sub>*S*, *CO*, *O*<sub>2</sub>: *Plug-in electrochemical cell* 

Combustible: Plug-in infrared (IR) or catalytic bead

**User Options** User Message Maintenance Notification

TWA/STEL Intervals

Language (6)

Sensor Disable

Safe Display

Self-Test Lock

Auto-zero on start up

Bump Test Interval

Low/High Alarm

TWA Method

Calibration

Sensor Disable

Dock Lock

Calibration gas

Calibration Interval

TWA/STEL Alarm



Portable gas detectors you can count on.